



advantage range **KKR1401**

ø140 (5.5") Single plate rally clutch

Applications:
General rally use



Specifications

	KKR1401HORSR01	KKR1401HDGSR01
Dynamic Torque Capacity Nm (lb/ft)	228 (168)	317 (233)
Release ratio	Hlgh	HIGH
Assembly Weight inc. Driven Plate (Kg)	1.90	1.90
Assembly Inertia inc. Driven Plate (Kgm ²)	0.0062	0.0062
Release Load New ø38 Bearing (kN)	2.3	2.9
Release Load New ø44 Bearing (kN)	2.6	3.2
Release Load New ø52 Bearing (kN)	2.9	3.5
Step flywheel part numbers shown. For Pot flywheel replace "SR" with "PR"		

Replacement parts

Part Number	KKR1401HORSR01	KKR1401HDGSR01
Pressure Plate (High Ratio)	KPS140L6H450	KPS140L6H450
Pressure Plate Thickness (mm)	11.5	11.5
Pressure Plate Fulcrum Dia (mm)	Ø117	Ø117

Key features and benefits

- Compact design for low weight and inertia.
- High stiffness cover design for improved start line control.
- Open lug type design for improved cooling and dust removal.
- Durable plated finish.
- Stainless steel wear plates fitted to cover lugs.
- Interchangeable with other manufacturers' products.
- Step and Pot flywheel mounting options available.

Installation dimensions

